



# DATASHEET APSYN140

## Specification V1.14

Wideband Synthesizer

8 kHz to 40 GHz



# CONTENTS

<b>Definitions.....</b>	<b>3</b>
<b>Introduction.....</b>	<b>3</b>
<b>Facts &amp; Figures &amp; Specifications.....</b>	<b>4</b>
Signal Specifications .....	4
Frequency Reference .....	4
Level Performance.....	4
Reverse Power Protection and VSWR.....	5
Phase Noise .....	5
Spectral Purity .....	7
Modulation Capabilities .....	8
Pulse Modulation .....	8
Internal pulse generator.....	8
Frequency Modulation .....	9
Phase Modulation .....	9
Sweeping Capability .....	9
Trigger (TRIG IN): Input is TRIG IN at front panel.....	9
Connectors .....	10
Standard Front.....	10
Standard Rear.....	10
Front with option TOUCH.....	11
Rear with option TOUCH .....	11
<b>Ordering Information .....</b>	<b>12</b>
<b>General Characteristics.....</b>	<b>13</b>
Document History .....	14
<b>Notes.....</b>	<b>15</b>

## DEFINITIONS

- The specifications in the following pages describe the warranted performance of the instrument for  $23 \pm 5$  °C after a 30-minute warm-up period

**Typical:** Expected mean values, not warranted performance

**Min and max:** Parameter range that is guaranteed by product design, and/or production tested. Warranted performance specifications include guard-bands to account for the expected statistical performance distribution, measurement uncertainties, and changes in performance due to environmental conditions.

## INTRODUCTION

- **Ultra-compact, fast and ultra-low phase noise Frequency Synthesizer with USB & LAN interface**

The APSYN140 is a wideband low phase-noise synthesizer settable from 8 kHz to 40 GHz. The settable output power range is from -10 to +25 dBm.

The module has a milli-Hz frequency resolution and uses a high-stability internal reference. The internal reference can be phase-locked to a user-settable external reference. For highest phase coherence, multiple APSYN140 can be cascaded with just one master reference clock.

The APSYN140 offers dedicated sweeping capabilities with switching speeds of only 500 µs (20 µs with option FS) and internal phase and narrow pulse modulation.

The module has USB and LAN interfaces and can be controlled using the SCPI 1999 command set. Operated with an external 24V DC supply, it consumes less than 25 W.

# FACTS & FIGURES & SPECIFICATIONS

## Signal Specifications



PARAMETER	MIN	TYPICAL	MAX	NOTE
<b>Frequency Range</b>	100 kHz 8 kHz		40 GHz 40 GHz	Settable from 100 kHz to 43.5 GHz Option 8K
Resolution		0.001 Hz		
<b>Phase Resolution</b>		0.01 deg		
<b>Switching Speed</b>		1.5 ms		after SCPI command received
CW Mode		500 µs		
Sweep / List Mode		500 µs 20 µs		Option FS

## Frequency Reference

PARAMETER	MIN	TYPICAL	MAX	NOTE
<b>Internal reference frequency</b>		100 MHz 10 MHz		Option LN
<b>Internal Reference Output Frequency</b>				
Temperature stability			±100 ppb ±20 ppb	0 to 50 degC Option LN / LN+
Aging 1st year			1 ppm 0.03 ppm 0.02 ppm	Option LN Option LN+
Aging per day			5 ppb 0.5 ppb < 0.5 ppb	after 30 days operations Option LN Option LN+
Warm-up time		5 min		
Output of internal reference		100 MHz		
		10 / 100 MHz		Option LN / LN+
Output power	0 dBm	5 dBm		
Output impedance		50 Ohms		
<b>Bypass Internal reference Input</b>		100 MHz		High phase synchronous mode *Options LN/LN+ are bypassed
<b>Phase Lock to External Reference</b>	1 MHz	10 MHz integer MHz	250 MHz	Option VREF *Options LN/LN+ are bypassed
Reference Bypass Mode		100 MHz		
<b>Reference input level</b>				
10 MHz or 1-250 MHz	-5 dBm	0 dBm	+13 dBm	
Bypass 100 MHz	5 dBm		+15 dBm	
<b>Reference input impedance</b>		50 Ohm		
<b>Lock Range</b>				
10 MHz or 1-250 MHz			±1.5 ppm	
Bypass 100 MHz			>100 ppm	

## Level Performance

PARAMETER	MIN	TYPICAL	MAX	NOTE
<b>Output power level</b>				(see also plot)
10 MHz to 1.2 GHz	0 dBm		+20 dBm +18 dBm	Option FILT
1.2 GHz to 20 GHz	-10 dBm		+20 dBm +13 dBm	Option FILT
20 to 30 GHz	10 dBm		+20 dBm +13 dBm	Option FILT
30 to 40 GHz	0 dBm		+18 dBm +10 dBm	Option FILT
<b>Power Resolution</b>		0.5 dB		
<b>Power Accuracy</b>		±0.5 dB	±2 dB	

**Figure 1: Maximum Output Power (Standard)****Figure 2: Maximum Output Power with FILT**


### Reverse Power Protection and VSWR

PARAMETER	MIN	TYPICAL	MAX	NOTE
<b>Reverse Power Protection</b>				
DC Voltage		7 V		
RF Power			20 dBm	
<b>Output impedance</b>		50 Ohm		
VSWR		1.8		


### Phase Noise

PARAMETER	MIN	TYPICAL	MAX	NOTE
<b>SSB Phase noise at 1 GHz</b>				(see also plot)
at 10 Hz from carrier		-93 dBc/Hz		Option LN / LN+
at 1 kHz from carrier		-130 dBc/Hz		
at 100 kHz from carrier		-145 dBc/Hz		
Wideband noise		-160 dBc/Hz		
<b>SSB Phase noise at 10 GHz</b>				
at 10 Hz from carrier		-73 dBc/Hz		Option LN / LN+
at 1 kHz from carrier		-110 dBc/Hz		
at 100 kHz from carrier		-125 dBc/Hz		
Wideband noise		-160 dBc/Hz		


**Figure 3: Phase Noise Performance with Option LN**



**Figure 4: Phase Noise Performance without Option LN (10, 20, 30, 40 GHz)**




**Figure 5: Amplitude Noise at 10 GHz**




## Spectral Purity

PARAMETER	MIN	TYPICAL	MAX	NOTE
Output harmonics		-15 dBc	-55 dBc	-45 dBc Option FILT, > 1 GHz
Sub-harmonics		-75 dBc	-45 dBc	< 20 GHz
Non-harmonic spurious		-75 dBc	-60 dBc	>20 GHz

**Figure 6: Harmonics @ 0 dBm (with option FILT)**



**Figure 7: Harmonics +15 dBm (with option FILT)**






## Modulation Capabilities

### Pulse Modulation

PARAMETER	MIN	TYPICAL	MAX	NOTE
Modulation source		Internal/ External		
Pulse rise/fall time		10 ns		
On/off ratio		40 dB		$P_{out} > +10 \text{ dBm}$ , see plot
Pulse overshoot			10%	
Pulse delay		20 ns		
Pulse polarity		Normal, inverse		selectable
External input threshold	0.85 V	0.9 V	0.95 V	TTL compatible
External input voltage range	-0.5 V		+5.5 V	TTL compatible
External input hysteresis		60 mV		

Figure 8: Pulse Modulation on-off ratio



### Internal pulse generator

PARAMETER	MIN	TYPICAL	MAX	NOTE
Repetition frequency (PRF)	0.1 Hz		100 MHz	$= 1/T$
Duty cycle	1 % to 99 % in 1% steps			within specified minimum pulse width
Pulse width settling range	30 ns		5 s	
Pulse Pattern Modulation & Staggered PRF				Using internal pattern generator
Programmable pattern length	2		65536	
Duty cycle	0.05%		99.95%	
Pulse period (T) accuracy		0.00005xT+ 3ns		
Pulse width accuracy		0.00005xT+ 5ns		
Pulse width resolution		5 ns		
Pulse jitter		2 ns	5 ns	
Polarity		selectable		

## Frequency Modulation

PARAMETER	MIN	TYPICAL	MAX	NOTE
<b>Frequency Modulation</b>				
Modulation source		Internal		
Maximum Frequency deviation (peak)		N · 400 MHz		< 1.25 GHz (N=1) 1.25 GHz to 2.5 GHz (N=0.125) 2.5 GHz to 5 GHz (N=0.25) 5 GHz to 10 GHz (N=0.5) 10 GHz to 20 GHz (N=1) 20 GHz to 40 GHz (N=2)
Deviation accuracy		0.50%	2%	
Distortion (THD)		< 1 %		1 kHz rate, 10 kHz deviation
Modulation rate	0.1 Hz		80 kHz	
Modulation waveforms	Sine			

## Phase Modulation

PARAMETER	MIN	TYPICAL	MAX	NOTE
Modulation source		Internal		
Phase deviation (peak)	0		300 · N· rad	
Deviation accuracy		0.50%	2%	
Modulation rate	0.1 Hz		80 kHz	
Modulation waveforms		Sine		
Distortion (THD)		< 1%		1 kHz rate & N x rad deviation

## Sweeping Capability

Sweep type: linear, logarithmic, random

PARAMETER	MIN	TYPICAL	MAX	NOTE
<b>Frequency Sweep</b>				
Step time ( $t_{step}$ )	500 µs 20 µs			Option FS
Dwell time ( $t_{dwell}$ )	15 µs			

## Trigger (TRIG IN): Input is TRIG IN at front panel

PARAMETER	MIN	TYPICAL	MAX	NOTE
<b>Trigger Types</b>	Continuous, single (point), gated, gated direction			
<b>Trigger Source</b>	external, bus (LAN, USB)			
<b>Trigger Modes</b>	Continuous free run, trigger and run, reset and run			
Trigger latency		5 ns		
Trigger uncertainty		10 ns		
External Trigger delay	50 ns		40 s	
External Delay Resolution		5 ns		
<b>Trigger Modulo</b>	1		255	Execute only on Nth trigger event
<b>Trigger Polarity</b>	Rising, falling			
<b>External trigger input threshold</b>	0.85 V	0.9 V	0.95 V	TTL compatible
<b>External trigger input voltage range</b>	-0.5 V		+5.5 V	TTL compatible
<b>External trigger input hysteresis</b>		60 mV		



## Connectors

### Standard Front




1. Power switch
2. RF connector K-type (female)
3. REF IN External reference input: BNC female
4. REF OUT Internal reference output: BNC female
5. PULSE Pulse modulation input: BNC female
6. TRIG Trigger input: BNC female

### Standard Rear




1. DC Power plug (24 V, 3 A)
2. LAN connection RJ-45
3. USB 2.0 host and device

## Front with option TOUCH



- Rotary Button** The rotary button is used to change the value selected on the screen.
- RF 50 Ω connector** This female K-type connector provides the output for generator signals. The impedance is 50 ohm. The reverse power damage level is +20 dBm maximum. The maximum allowed DC level is +/- 7 V. Please check the data sheets for more details.

## Rear with option TOUCH



- REF IN** External reference input: BNC female
- MOD IN** Modulation input for FM/PM: BNC female
- TRIG IN** Trigger input: BNC female
- LAN connection** RJ-45
- USB 2.0** host and device
- REF OUT** Internal reference output: BNC female
- PULSE IN** Pulse modulation input: BNC female
- TRIG OUT** Trigger output: BNC female
- DC power switch**
- DC Power plug** (24 V, 3 A)

## ORDERING INFORMATION

HOST MODEL	PRODUCT	DESCRIPTION
<b>APSYN140</b>	<b>APSYN140</b>	100 kHz to 40 GHz Synthesizer, flange-mount module
<b>APSYN140</b>	<b>Option 8K</b>	Frequency range extension to 8 kHz
<b>APSYN140</b>	<b>Option LN</b>	Enhanced close in phase noise & frequency stability
<b>APSYN140</b>	<b>Option LN+</b>	Enhanced close in phase noise & further enhanced long term frequency stability
		External power bank adapter cable
<b>APSYN140</b>	<b>Option EB</b>	
<b>APSYN140</b>	<b>Option FILT</b>	Improved harmonic rejection (only in combination with Option TOUCH)
<b>APSYN140</b>	<b>Option FS</b>	Ultra-fast switching speed
<b>APSYN140</b>	<b>Option TOUCH</b>	Desktop / Portable instrument with color touch display 
<b>APSYN140</b>	<b>Option DATA</b>	Commercial Calibration Certificate with test data (per channel)
<b>APSYN140</b>	<b>Option IEC</b>	IEC 17025 calibration with certificate
<b>APSYN140</b>	<b>Option FLASH</b>	MicroSD card slot for removable SD memory
<b>APSYN140</b>	<b>Retrofit</b>	Applies when options are back-ordered per channel
<b>APSYN140</b>	<b>Option VREF</b>	Variable external reference
<b>APSYN140</b>	<b>Option WE</b>	One year warranty extension (standard: 2 years)
<b>APSYN140</b>	<b>Option ReCal</b>	Recalibration with certificate (recommended: 2 years interval)

## GENERAL CHARACTERISTICS

### Remote programming interfaces

Ethernet 100BaseT LAN interface, USB 2.0, Control language SCPI Version 1999.0

### Power requirements 24V ± 3.0 VDC; 25 W maximum

**Mains adapter supplied:** 100-240 VAC in/ 24 V 4.0 A DC out

**Environmental** (Levels similar to MIL-PRF-28800F Class 3/4)

**Operating temperature range** 0 to 45 °C

**Storage temperature range** -40 to 70 °C

**Operating and storage altitude** up to 15,000 feet (4600 m)



Safety/EMC complies with applicable Safety and EMC regulations and directives.

**Weight:** ≤ 1.0 kg (2.2 lbs) net

**Dimensions (W x L x H):** 10.5 x 27 x 6 cm [4.13 x 10.63 x 2.36 in]

## Document History

Version/Status	Date	Author	Notes
V10	2018-05-01	jk	first release
V101	2018-08-13	jk	
V102	2018-11-27	jk	Power ranges, Pictures, Ordering Info
V103	2018-12-10	mm	Introduction text
V1031	2019-01-28	db	Output of internal reference: 100 MHz
V104	2019-03-18	jk	Corrections
V110	2020-09-15	jk	Max power plot
V111	2021-02-25	db	Pulse and trigger input electrical specifications
V112	2022-11-18	yg	Add option FILT, TOUCH
V113	2022-10-02	ap/ee	Added option LN+, updated layout
V114	2024-02-07	ap/mh/yg	External reference mode amendment

## AnaPico of Switzerland

Europa-Strasse 9  
8152 Glattbrugg  
Switzerland

Phone +41 44 440 00 50  
Email sales@anapico.com

[www.anapico.com](http://www.anapico.com)  
[www.anapico.com/downloads/](http://www.anapico.com/downloads/)

## NOTES